GAS DETECTION PRODUCTS

BW GAS ALERT MICRO CLIP XL

MULTUI GAS DETECTOR 4 GASES (H2S CO O2 LEL)

Product Information

Use unique advanced technology for safety, compliance and productivity.

- **Advanced engineering for reliable battery performance**
- **Reflex™ Technology to ensure sensor responsiveness**
- **Compact, lightweight and easy to use – no expertise required**
- **Flashing green IntelliFlash™light for compliance at a glance**

OVERVIEW

- **Honeywell BW™ MicroClip X3 for extended reliability with 3-year warranty**
- **Honeywell BW™ MicroClip XL for standard operation with 2-year warranty**
- **Guaranteed to run an entire shift – even at -4°F (-20°C)**
- **Ip68 rating – unmatched water protection**
- **Compact, lightweight and easy to use – with one-button operation and no extensive training**
- **Device management with Honeywell Safety Suite.**

Hazards

H_2S
CO
O_2
LEL

Honeywell

GAS DETECTION PRODUCTS

BW GAS ALERT MICRO CLIP XL

MULTUI GAS DETECTOR 4 GASES (H2S CO O2 LEL)

Specification

▪ SIZE	11.3 x 6.0 x 3.2 cm / 4.4 x 2.4 x 1.2 in
▪ WEIGHT	190 g / 6.7 oz. 179 g / 6.3 oz.
▪ HUMIDITY	0% - 95% RH (non-condensing)
▪ TEMPERATURE	-20 to +50°C / -4 to +122°F
▪ ALARMS	Visual, vibrating, audible (95 dB) • Low, High, TWA, STEL, OL (over limit)
▪ TESTS	Audible/visual alarms on activation; sensors, battery and circuitry (continuous)
▪ TYPICAL BATTERY LIFE	18 hours; recharges in less than 6 hours
▪ USER OPTIONS	Confidence beep Set STEL interval Sensor on/off Latching alarms Safe display mode Stealth mode Calibration lock Auto zero on start up Oauto calibration on start up Set bump test interval Force bump test when overdue IntelliFlash™ interval Combustible gas measurement (%LEL or % by volume methane) User-settable calibration gas level Force calibration when overdue Low alarm acknowledge Language choices Set custom start up message
▪ RATINGS	Ip68 - up to 45 minutes at 1.2 m (GasAlertMicroClip XL and X3) EMI/RFI: Complies with EMC Directive 2004/108/EC

CERTIFICATIONS AND APPROVALS

CSA: Class I, Div. 1, Gr. A, B, C, D

IECEx: Ex ia IIC T4 Ga

ATEX: II 1 G Ga Ex ia IIC T4

CE European Conformity

KTL (GasAlertMicroClip X3 certification in progress)

Warranty

Five years including all sensors* (GasAlertMicroClip X3 only)

Warranty

GAS	MEASURING RANGE	RESOLUTION
H2S	0 -100 ppm	1 ppm
CO	0 - 500 ppm	1 ppm
O2	0-30.0%	0.1%
COMBUSTIBLE GASES	0-100% LEL	1%
	0-5.0% v/v	0.1%

Honeywell