



1610 PROTECTOR CASE

FEATURES

- Interior: 21.8" × 16.7" × 10.6"
- Watertight, crushproof, and dustproof
- Strong polyurethane wheels with stainless steel bearings
- 3 level Pick N Pluck™ with convoluted lid foam
- Open cell core with solid wall design - strong, light weight
- Retractable extension handle
- Fold down handles

SPECIFICATION

• Interior (L×W×D)	21.78 x 16.69 x 10.62 in (55.3 x 42.4 x 27 cm)
• Exterior (L×W×D)	24.83 x 19.69 x 11.88 in (63.1 x 50 x 30.2 cm)
• Lid Depth	2.05" (5.2 cm)
• Bottom Depth	8.57" (21.8 cm)
• Total Depth	10.62" (27 cm)
• Int Volume	2.23 ft ³ (0.063 m ³)
• Padlock Hole Diameter	5/16" (8 mm)
• Weight With Foam	22.30 lbs (10.1 kg)
• Weight Empty	19.50 lbs (8.8 kg)
• Buoyancy	119.93 lbs (54.4 kg)
• Body Material	Polypropylene
• Latch Material	ABS
• O-Ring Material	Polymer
• Pins Material	Stainless Steel
• Foam Material	1.3 lb Polyurethane
• Purge Body Material	ABS
• Purge Vent Material	3 Micron Hydrophobic Non-Woven
• Foam Layer 1 (Lid)	2.00" (5.1 cm) - Convoluted
• Foam Layer 2 (Base)	2.38" (6 cm) - Pick N Pluck (.50" x .50" squares)
• Foam Layer 3 (Base)	2.38" (6 cm) - Pick N Pluck (.50" x .50" squares)
• Minimum Temperature	-40° F (-40 ° C)
• Maximum Temperature	210° F (99 ° C)

COLORS

Black, Desert Tan

CERTIFICATIONS

Ip67 / STANAG 4280 / Def Stan 81-41

