



## Select Flow Nozzle RB 101 NFPA

The Rosenbauer SELECT FLOW nozzle enables the manual adjustment of the water flow rate via an adjusting ring. This achieves a maximum extinguishing effect with minimal water consumption. The nozzles of the SELECT FLOW RB 99 EN, RB 100 EN and RB 101 EN series are TÜV Austria certified according to the

According to EN 15182-2:2007

	RB 99 EN	RB 100 EN	RB 100D EN	RB 101 EN
Adjustable	17	45	45	130
Flow rate in l/min	30	85	85	230
	80	130	130	300
	130	200	235	400

Maximum throw range	ca. 32 m	ca. 36 m	ca. 36 m	ca. 44 m
---------------------	----------	----------	----------	----------

Length	30 cm	30 cm	30 cm	31 cm
--------	-------	-------	-------	-------

Weight	2 kg	2 kg	2 kg	2.2 kg
--------	------	------	------	--------

### Features

- Rotating stainless steel toothed ring
- Pistol handgrip
- Impact resistant adjusting ring
- Ergonomic open/close clip, with glass-fiber reinforced plastic and aluminum insert
- Shortened rotational path
- High-quality materials

### Suitable for

- Interior
- Exterior
- Penetration
- Protection
- Ventilation

### Certifications

- EN 15182-2:2007.

